




0.6/1kV HF-EPR Insulated, SW2/SW4 Sheathed Armoured Fire Resistant Power & Control Cables

Application

These fire resistant elastomeric insulated cables are designed for fixed wiring in ships and on mobile offshore units, suitable for use in power and control applications where fire integrity is essential.

Standards

- BS 7917
- IEC 60331-31 Fire resistant
- IEC 60332-3A Flame retardant
- IEC 60754-1; IEC 60754-2 Corrosivity
- IEC 61034-2 Smoke density
- Cold bend and impact (-40°C) (on request)
- CSA C22.2 No. 38-95 (on request)



- Stranded Tinned Copper Conductor
- Mica Tape+HF-EPR GP4 Insulation
- SB1 Inner Sheath
- Galvanized Steel Wire/Tinned Bronze Wire Braid
- SW2/SW4 Outer Sheath

Construction

- Conductor: Tinned copper wire stranded circular cl. 2 BS 6360/IEC 60228.
- Insulation: Mica tape + HF-EPR GP4 according to BS 7655 1.2.
- Inner Sheath: Halogen free thermosetting compound SB1 according to BS 7917.
- Armour: Galvanized steel wire braid or tinned bronze wire braid (single core). Copper wire braid can be offered upon request.
- Outer Sheath: Halogen free thermosetting compound SW4 according to BS 7655 2.6 or reduced halogen thermosetting compound SW2 according to BS 7655 2.6.

Mechanical and Thermal Properties

Minimum Internal Bending Radius: $6 \times OD$
Temperature Range: -40°C ~ +90°C



Dimensions and Weight

Single core cables

Construction No. of cores×Cross section(mm ²)	Nominal Insulation Thickness mm	Nominal Inner Sheath Thickness mm	Minimum Diameter Over Inner Sheath mm	Maximum Diameter Over Inner Sheath mm	Nominal Armour Wire Diameter mm	Nominal Outer Sheath Thickness mm	Minimum Overall Diameter mm	Maximum Overall Diameter mm	Approx. Weight kg/km
1×4	1.0	1.0	6.7	8.0	0.3	1.1	10.2	12.1	245
1×6	1.0	1.0	7.2	8.5	0.3	1.1	10.8	12.6	275
1×10	1.0	1.0	8.1	9.5	0.3	1.2	11.9	13.8	355
1×16	1.0	1.1	9.3	10.7	0.3	1.2	13.1	15.0	440
1×25	1.2	1.2	11.5	13.2	0.3	1.3	15.4	17.7	600
1×35	1.2	1.2	12.3	14.1	0.3	1.4	16.5	18.8	720
1×50	1.4	1.3	14.1	15.9	0.3	1.4	18.2	20.6	910
1×70	1.4	1.3	15.8	17.8	0.3	1.5	20.2	23.0	1170
1×95	1.6	1.4	18.1	20.2	0.3	1.6	22.6	25.6	1510
1×120	1.6	1.5	20.0	22.4	0.3	1.7	24.7	27.7	1830
1×150	1.8	1.6	22.0	24.6	0.3	1.8	26.9	30.1	2160
1×185	2.0	1.7	24.4	27.0	0.45	1.9	30.2	33.9	2790
1×240	2.2	1.8	27.5	30.3	0.45	2.0	33.5	37.3	3530
1×300	2.4	1.9	30.4	33.6	0.45	2.1	36.6	40.5	4280

Multicore cables

Construction No. of cores×Cross section(mm ²)	Nominal Insulation Thickness mm	Nominal Inner Sheath Thickness mm	Minimum Diameter Over Inner Sheath mm	Maximum Diameter Over Inner Sheath mm	Nominal Armour Wire Diameter mm	Nominal Outer Sheath Thickness mm	Minimum Overall Diameter mm	Maximum Overall Diameter mm	Approx. Weight kg/km
2×1.5	0.8	1.1	9.0	10.4	0.3	1.2	12.7	14.7	310
2×2.5	0.8	1.1	9.8	11.4	0.3	1.2	13.6	15.5	355
2×4	1.0	1.2	11.8	13.5	0.3	1.3	15.7	18.0	475
2×6	1.0	1.2	12.9	14.6	0.3	1.4	17.0	19.3	580
2×10	1.0	1.3	14.9	16.8	0.3	1.4	19.0	21.4	750
2×16	1.0	1.4	17.1	19.1	0.3	1.5	21.4	24.3	980
2×25	1.2	1.5	21.2	23.7	0.3	1.7	25.9	29.0	1380
2×35	1.2	1.6	23.1	25.7	0.3	1.8	28.0	31.2	1710
2×50	1.4	1.7	26.5	29.2	0.45	2.0	32.5	36.3	2370
2×70	1.4	1.9	30.3	33.5	0.45	2.1	36.5	40.5	3100
2×95	1.6	2.1	34.9	38.2	0.45	2.3	41.4	46.0	4020
2×120	1.6	2.2	38.4	42.2	0.45	2.5	45.4	50.1	4870
3×1.5	0.8	1.1	9.6	11.0	0.3	1.2	13.3	15.3	345
3×2.5	0.8	1.1	10.4	12.1	0.3	1.3	14.4	16.4	405
3×4	1.0	1.2	12.6	14.3	0.3	1.3	16.5	18.8	540
3×6	1.0	1.2	13.8	15.5	0.3	1.4	17.9	20.2	660
3×10	1.0	1.3	15.9	17.8	0.3	1.5	20.2	23.0	910
3×16	1.0	1.4	18.2	20.3	0.3	1.6	22.8	25.7	1200



Caledonian

Any inquiries, please feel free to contact
enquiry@shipboard-cables.com or sales@shipboard-cables.com



Construction No. of cores×Cross section(mm ²)	Nominal Insulation Thickness mm	Nominal Inner Sheath Thickness mm	Minimum Diameter Over Inner Sheath mm	Maximum Diameter Over Inner Sheath mm	Nominal Armour Wire Diameter mm	Nominal Outer Sheath Thickness mm	Minimum Overall Diameter mm	Maximum Overall Diameter mm	Approx. Weight kg/km
3×25	1.2	1.6	22.9	25.4	0.3	1.8	27.8	30.9	1760
3×35	1.2	1.7	24.9	27.6	0.45	1.9	30.7	34.4	2260
3×50	1.4	1.8	28.5	31.3	0.45	2.0	34.5	38.4	2880
3×70	1.4	2.0	32.7	35.9	0.45	2.2	39.0	43.5	3800
3×95	1.6	2.2	37.5	41.0	0.45	2.4	44.3	48.9	4890
3×120	1.6	2.3	41.3	45.3	0.45	2.6	48.5	53.7	6070
3×150	1.8	2.5	45.8	49.9	0.45	2.8	53.3	58.7	7270
3×185	2.0	2.7	50.9	55.5	0.45	3.0	58.8	64.9	8970
3×240	2.2	2.9	57.5	62.4	0.45	3.2	65.8	72.2	1350
4×1.5	0.8	1.1	10.5	12.1	0.3	1.3	14.4	16.4	395
4×2.5	0.8	1.1	11.4	13.1	0.3	1.3	15.4	17.6	465
4×4	1.0	1.2	13.8	15.6	0.3	1.4	17.9	20.3	640
4×6	1.0	1.3	15.3	17.3	0.3	1.5	19.6	22.5	790
4×10	1.0	1.4	17.7	19.7	0.3	1.6	22.2	25.1	1070
4×16	1.0	1.5	20.3	22.8	0.3	1.7	25.0	28.1	1460
4×25	1.2	1.7	25.5	28.1	0.45	1.9	31.3	35.0	2140
4×35	1.2	1.8	27.7	30.5	0.45	2.0	33.7	37.5	2670
4×50	1.4	1.9	31.8	35.0	0.45	2.2	38.1	42.1	3630
4×70	1.4	2.1	36.3	39.7	0.45	2.4	43.1	47.7	4740
4×95	1.6	2.3	41.7	45.7	0.45	2.6	48.9	54.1	6290
4×120	1.6	2.5	46.2	50.3	0.45	2.8	53.7	59.2	7670
5×1.5	0.8	1.1	11.4	13.1	0.3	1.3	15.4	17.6	455
7×1.5	0.8	1.2	12.6	14.4	0.3	1.3	16.6	18.9	530
12×1.5	0.8	1.3	16.8	18.8	0.3	1.5	21.2	24.0	790
19×1.5	0.8	1.4	19.9	22.4	0.3	1.6	24.4	27.5	1080
27×1.5	0.8	1.6	24.3	26.9	0.3	1.8	29.2	32.8	1460
37×1.5	0.8	1.7	27.4	30.4	0.45	1.9	33.2	37.0	1990
5×2.5	0.8	1.2	12.7	14.4	0.3	1.3	16.6	18.9	560
7×2.5	0.8	1.2	13.9	15.6	0.3	1.4	18.0	20.3	650
12×2.5	0.8	1.4	18.7	20.8	0.3	1.6	23.2	26.2	970
19×2.5	0.8	1.5	22.1	24.7	0.3	1.7	26.8	30.0	1360